

UX5000 Clamp-on Flow Meter for use in Hazardous Environments.

FEATURES:

- Non-invasive, efficient, and easy installation, no process downtime
- Certified for use in hazardous areas (Zone 1 and Zone 2),
- Intrinsically Safe Measurement System including matched, wet calibrated transducers.
- Reliable measurement accuracy
- Separate Display (DCSIU) and Measurement Unit (RMU) allows flexibility in installation.
- Cost effective metering for harsh, heavy-duty applications.

APPLICATIONS:


- Applications for the UX5000 are vast. The UX5000 is ideal for harsh, heavy duty industrial applications for measuring flow of liquid in pipes – non-invasively. It is especially well-suited to the chemical, water and oil industries, typical applications include:
- Liquid flow hydrocarbons in oil industry
- Flow Measurement in Chemical Industry
- Heavy Industry Process Liquid Measurement



MEASUREMENT PRINCIPLES:

The UX5000 uses a cross correlation transit time algorithm to provide accurate flow measurements. An ultrasonic beam of a given frequency is generated and applied to the transducer crystals. This transmission goes first from the downstream transducer to the upstream transducer as shown in the upper half of Figure 1. The transmission is then made in the reverse direction, being sent from the upstream transducer to the downstream transducer as shown in the lower half of Figure 1. The speed at which the ultrasound is transmitted through the

liquid is increased slightly by the velocity of the liquid through the pipe. The subsequent time difference $T1 - T2$ is directly proportional to the liquid flow velocity.



$$T1 - T2 + K \cdot dt = \text{flow velocity}$$

UX5000 Clamp-on Flow Meter

TECHNICAL SPECIFICATION:



| | |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Measurement Principle | Transit Time difference |
| Measurement Channels | 1 or 2 Channel Option. Single or Multiple Path Configuration |
| Measurement Uncertainty | ±0.5%* |
| Repeatability | +/- 0.15% of measured value |
| Applicable Fluid Types | All acoustically conductive liquids with <3 % Particulate – Air/solids |
| Pipe Material | Steel, Stainless Steel, Copper, Plastic Pipes For other materials please contact technical team. |
| Pipe Diameter Range | 4" to 12" Pipe. (100-300mm) |
| Volumetric Flow Units | litres/sec, litres/min; gal/hr, gal/min, gallons/sec; m ³ /min, m ³ /hour; US gal/sec, US gal/min, US gal/hr |
| Flow Velocity Units | m/s, ft/s |
| Volume Units | Litres, m ³ , gal, US gal |
| Mass | Kg, lbs |
| Temp | °C, °F |
| Display Unit (DCSIU) | |
| Marking | Ex II 2 (I)G Ex db [Ex ia] IIC T4 Gb (-20°C<Tas+60°C) |
| Protection Rating | IP66 |
| Mounting Options | Wall or Pipe |
| Material | Marine Grade Aluminium |
| Power supply | 19 to 29V DC |
| Display | Graphical LCD Display |
| Remote Housing Unit (RMU) | |
| Marking | Ex II 2 (1) G Ex db [Ex ja] IIC T4 Gb (-20 °C<Ta<+60 °C) |
| Protection Rating | IP66 |
| Mounting Options | Wall or Pipe |
| Material | Painted Cast Aluminium |
| Intrinsically Safe Transducers | |
| Type B | 1 MHz |
| Marking | Ex II 2 (1) G Ex db [Ex ja] IIC T4 Gb (-20 °C<Ta<+60 °C) |
| Protection Rating | IP67 |
| Mounting | Pipe Mounted Guide Rail |
| Coupling Material | Gel Pads, Grease |
| Temperature Sensor | |
| Type | Pt100 Class B 4 wire |
| Range | -20°C to 135°C (-4 to 275°F) |
| Mounting | Stainless Steel Cable Tie |
| Packaging | |
| Dims | 375x375x300mm |
| Weight | 10kg |
| Certification | |
| ATEX | CML 22ATEX2388X |
| UKEX | CML 22UKEX2389X |
| IECEx | IECEx CML 22.0052X |

* Sensor Calibration on Test Rig

www.bhydroservis.sk
0905 316 728

